



### NOTES:

1. 20 FEET DRIVEWAY ENTRANCES SHALL BE USED ON COLLECTOR AND ARTERIAL STREETS.
2. RESIDENTIAL DRIVEWAYS SHALL NOT BE CONSTRUCTED IN THE RADIUS OF A CORNER LOT.
3. VDOT STANDARDS MAY BE SUBSTITUTED IF APPROVED BY CITY ENGINEER.
4. GRAVEL DRIVEWAYS ON COLLECTOR AND ARTERIAL STREETS SHALL BE PAVED A MINIMUM OF 10 FEET FROM EDGE OF CURB OR TO THE RIGHT-OF-WAY LINE, WHICHEVER IS GREATER.
5. ENTIRE ENTRANCE INCLUDING GUTTER AND APRON SHALL BE POURED MONOLITHICALLY.
6. WIDTH OF CURB & GUTTER SHALL MATCH WIDTH OF EXISTING CURB & GUTTER.



## THE CITY OF LYNCHBURG

### RESIDENTIAL DRIVEWAY ENTRANCE

USE WITH THE CITY OF LYNCHBURG STANDARD SPECIFICATIONS ONLY

SCALE:  
NOT TO SCALE

DETAIL #  
**25.11**

REVISION DATE:  
10-21-04

SHEET #:  
1 OF 1